Bullet Camera

4MP IP Camera

NC-4M-B31AF




KEY FEATURES:

- 4MP High resolution
- 3D DNR/D-WDR
- Triple streams
- 3.3~10.5mm, Motorized Lens
- · Auto focus: Motorized VF lens
- Alarm/Audio
- Built-in PoE/12VDC
- Reset button

DIMENSIONS

Unit: Inches (mm)



TECHNICAL SPECIFICATIONS

| Product Model | HD Auto Focus Lens IP Camera |
|-----------------------|---|
| Sensor | 1/3" 4.0Mega progressive scan CMOS |
| Min. illumination | Colour.0.01Lux/F1.2: 0Lux/F1.2(IR 0N) |
| Lens | 3.3~10.5mm Motorized lens |
| IR distance | 50 M |
| Electronic shutter | Auto(1/25s-1/10000s Adjustable) |
| Day/Night | Auto/Color / B&W (IR_CUT) |
| Noise Reduction | 2D/3D Digital Noise Reduction |
| Anti-fog | Support |
| WDR | Digital WDR |
| Image Adjustment | Sharpness, Brightness, Saturation, Contrast Adjustable |
| Video Encoding | H.264, H.265 |
| Encoding Type | H.265:MainProfile: H.264:High Profile/Main Profile/BaseLine Profile |
| Record Resolution | Main Stream:2560*1440@20fps |
| | Sub Stream: 704*576@20fps |
| | Third Stream: 1280*720@15fps |
| Video Bitrate Control | Support VBR/CBR |
| Video Bitrate Range | 32Kbps ~ 8Mbps |
| Audio | 1 Audio Input: 1 Audio Output |
| Alarm | 1 Alarm Input: 1 Alarm Output |
| Storage | Support TF Card, Max 64G |
| RS485 | Support |
| Reset Button | Built-in reset button |
| CVBS output | Support |
| Network Interface | RJ45 10M/100M adaptive Ethernet interface |
| Motion Detetion | Multiple detection zones, variable sensitivity levels |
| ROI | Support |
| Corridor Mode | Support |
| Privacy Masking | Four zones for privacy masking |
| Snapshot | JPEG capture, capture resolution is the max coding resolution |
| Security Features | Support password protection, watermarking features |
| Text Overlay | Support (Channel name and time title) |
| Alarm | Support network anomaly, mask alarm and etc |
| Intelligent Function | Support line-crossing detection |
| Mobile APP | IOS, Andriod |
| Network Function | TCP/IP: UDP: HTTP: IGMP: ICMP: DHCP: RTP/RTSP: DNS |
| | DDNS: FTP: NTP: PPPOE: UPNP: SMTP: SNMP |
| Protocol | Support ONVIF and CGI protocol |
| Protection Grade | IP66 |
| PoE | Support |
| Power | DC 12V |
| Operation Temperature | -10°C ~ +60°C |
| Operation Humidity | 10% ~ 90% |
| Power Supply | 10W MAX |
| Weight | 1200g |

^{*}Specifications are subject to change without any prior notice.