

Flush Mount Housing | SC-FMH

INSTALLATION INSTRUCTION

FEATURES



The Flush Mount Housing (SC-FMH) is designed to mount the EasyTrak™ PTZ speed dome camera to the suspended ceiling. Designed to make installation simple and easy, all that is required for installation is a Philips Screwdriver and a Ceiling Tile Cutter. Three Mounting Clamps are pre-attached on its sides to quickly and effectively join the housing to the ceiling tile.

Assembly Accessories

Safety Ring Cable	Self-tapping Screws
Q'ty : 1	Q'ty : 1
	Machine Screws
	Q'ty : 2

Specification



Construction	Aluminum, Acrylic Plastic
Finish	Light-gray Polyester Powder Coat.
Max. Load	6.6 lb (3Kg)
Environment	Indoor Only
Net Weight	2.2 lb (1Kg) w/ Heater & Blower
Power Source	24VAC
Temperature	32°F ~ 122°F (0°C ~ 50°C)
Dimensions	Unit: Inches (mm)



(Over)

HOW TO INSTALL

- Following the illustration on the right, install the Safety Ring Wire to the back of the Flush Mount Housing (SC-FMH) using the black machine screw.
- Remove the ceiling tile then draw a circle 7.25" (184mm) in diameter on the back. Cut out a hole using the Ceiling Tile Cutter.
- Place the housing inside the cut-out hole then mark the locations of the three Mounting Clamps. Make three notches roughly 1/2" tall and 1 1/2" wide to clear the Mounting Clamps.
- Once the hole and the notches have been cut out of the ceiling tile, insert the Flush Mount Housing (SC-FMH) making sure that the Mounting Clamps are not in the open position and are all in the closed position (Flush to the enclosure).
- When the housing is flush to the ceiling tile, open the Mounting Clamps then rotate the machine screws below to clamp down on the ceiling tile.
- Install the PTZ camera head to the base of the Flush Mount Housing (EasyTrak™ PTZ dome manual. 2.2.0 Mounting the EasyTrak™ PTZ Dome Camera), then close the dome cover over the housing. Turn the dome cover ring, not the actual dome, counter-clockwise to close.
- Take the entire assembly and set it down at the desired ceiling location. Secure the Safety Ring Wire to any suspended ceiling frame structure using the self-tapping screw.
- Join all the cable wires (power, comm., alarm, etc) together, then place all the loose wire inside the suspended ceiling.



NUVICO®

Tel: 201-541-1605 Fax: 201-541-1620
Email: techsupport@nuvico.com
www.nuvico.com

Version 1.1
Printed In Korea