

TN-EN12800 4K Resolution 128 Channel NVR

Highlights:

- 128 Channel IP
- RAID0, RAID1, RAID5, RAID6, RAID10
- Up to 8MP Resolution
- 384Mbps Max Throughput
- H.265 / H.264
- Up to 160TB Storage
- HDMI x 2 / VGA
- Xcel CMS and Mobile App Platform Compatible

Introduction:

The Nuvico Xcel TN-EN series is available in a 64 or 128 channel model supporting IP video. The TN-EN series utilizes the most advanced SOC techniques along with H.265 compression format to deliver real time recording, while maintaining quality and maximizing video storage and fluidity. Based on the Nuvico Xcel software platform, the TN-EN series features a mouse driven, clean GUI for easy local control, and is compatible with the Xcel CMS, Web CMS, and mobile apps.

Specifications:

SYSTEM				
Compression	Standard H.265 / H.264			
OS	Embedded Linux			
VIDEO				
Input	128 Channel IP			
Network Access Bandwidth	384Mbps			
Network Access Format	25/30fps @ 8MP, 5MP, 4MP, 3MP, 1080p, 960p, 720p			
Output	HDMI x 2: HDMI 1 at 4K, 1920x1080, 1280x1024, HDMI 2 at 1920x1080,1280x1024 VGA x 1: 1920x1080, 1280x1024			
AUDIO				
Output	RCA x 1			
Two-way Audio	RCA x 1			
RECORD				
Record Stream	Three-stream Recording			
Frame Rate	25/30fps @ 8MP, 5MP, 4MP, 3MP, 1080p, 960p, 720p			
Mode	Manual, Timer, Motion, Sensor			
PLAYBACK				
Simultaneous Playback	Max 16 Channels			
Search	Time Slice / Time / Event / Tag Search			
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events			
Function	Play, Pause, FF, FB, Digital Zoom, etc.			





















IP 8MP	H.265	DDNS	Network	Audio	Mic	Mouse Control	Notifications	
NETW	ORK							
Interface				RJ45 10/100/1000 Mbps x 2				
Protoco	ol			TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP				
Web CI	ient			Max 20 U	nline			
ALAR	M							
Mode			Manual, Sensor, Motion, Exception					
Input				8 Channel Local Alarm Input, 128 Channel IP Camera Alarm Input				
Output			4 Channel					
Triggering				Record, Snap, Preset, E-mail, etc.				
MOBII	LE DE\	/ICE						
os				iOS, Android				
STOR	AGE /	BACKI	JP					
HDD					SATA x 16, e-SATA x 1 Max 10TB Each HDD			
Disk Ar	Disk Array			RAID0, RAID1, RAID5, RAID6, RAID10				
Local Backup			U Disk, USB Mobile HDD					
Networ	k Backu	р		Yes				
Port								
USB					B 3.0 x 1 (Rear panel) B 2.0 x 2 (Front panel)			
GENE	RAL							
Power I	Power Requirement			ATX				
Power (Power Consumption				≤ 30W (without HDD)			
Workin	orking Environment			14°F ~ 122°F				
Relative	Humid	ity		10% ~ 90	~ 90%			
Weight				40 lbs (w/				
Form F	actor			3U Rackmount Case				
Dimens	ions			17.2" W x 19.02" D x 5.63" H				
Warran	ty			3 Years				
Packag	e Conte	nts		Recorder, Power Cord, Rack Mount Ears, USB Mouse				

Installation CD, Manual