

## TN-E1600AI-16P 4K Resolution 16 Channel NVR w/ Built-in 16 Port PoE

## **Highlights:**

- 16 Channel IP
- Up to 8MP Resolution
- 160Mbps Max Throughput
- H.265S / H.265+ / H.265 / H.264
- Up to 36TB Storage
- HDMI / VGA
- Free Xcel DDNS
- Xcel CMS and Mobile App Platform Compatible



The Nuvico Xcel TN-E AI series is available in a 8 or 16 channel model supporting IP video. The TN-E AI series utilizes the most advanced SOC techniques along with H.265S compression format to deliver real time recording, while maintaining quality and maximizing video storage and fluidity. Based on the Nuvico Xcel software platform, the TN-E AI series features a mouse driven, clean GUI for easy local control, and is compatible with the Xcel CMS, Web CMS, and mobile apps.

## **Specifications:**

SYSTEM		
Compression	H.265S / H.265+ / H.265 / H.264	
os	Embedded Linux	
VIDEO		
Input	16 Channel IP Camera Input	
Network Access Bandwidth	160Mbps	
IP Camera Encoding	25/30fps @ 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 1.3MP, 960p, 720p, 960H, D1, CIF	
Output	HDMI x 1: 4K, 2K, 1920 x 1080, 1280 x 1024, 1024 x 768 VGA x 1: 1920 x 1080, 1280 x 1024, 1024 x 768	
AUDIO		
Network Input	16 Channel Audio Input	
Output	RCA x 1	
Two-way Audio	RCA x 1	
RECORD		
Record Stream	Dual Stream Recording	
Resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 1.3MP, 960p, 720p, 960H, D1, CIF	
Mode	Manual, Timer, Motion, Sensor, POS, Al Recording	
PLAYBACK		
Simultaneous Playback	Max 16 Channels	
Search	Time Slice / Time / Event / Tag Search	
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events	
Function	Play, Pause, FF, FB, Digital	

Zoom, etc.

























11.2035 VCA B	DINO NELWOIK Addio	WIC WOUSE CONTROL NOTINGATIONS	
NETWORK			
Interface	RJ45 100	RJ45 1000 Mbps x 1	
PoE Port	RJ45 x 1	RJ45 x 16	
Protocol	DDNS, U	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, 802.1x, ONVIF	
Web Client	Max 10 L	Jsers Online	
ALARM			
Mode		Sensor, Motion, n, Smart Events	
Input		el Local Alarm Input, IP Alarm Input	
Output	4 Channe	el	
Triggering	Record, S E-mail, et	Snap, Buzzer, Preset, tc.	
<b>MOBILE DEVICE</b>			
os	iOS, Andı	roid	
STORAGE / BAC	KUP		
HDD	SATA x 2	, Max 18TB per HDD	
Local Backup	U Disk, U	ISB Mobile HDD	
Network Backup	Yes		
Port			
USB		x 1, USB 3.0 x 1 ( One in panel and one in the rear	
RS 485	Yes (Full- or Keybo	duplex), Connect to PTZ	
Remote Controller	Yes		
GENERAL			
Power Requirement	48VDC, 3	3.75A	
Power Consumption	ı ≤ 15W (w Power Sı	vithout HDD and PoE upply)	
Working Environme	<b>nt</b> 14°F ~ 12	22°F	
Relative Humidity	10% ~ 90	)%	
Weight	6.6 lbs (w	v/o HDD)	
Form Factor	1U Rackı	mount Case	
Dimensions	14.96" W	x 10.43" D x 1.77" H	
Warranty	3 Years		

Rackmount Ears