

5MP Flexible IP Weatherproof Bullet

NC-5M-B21

Specification



KEY FEATURES:

- 10pps @ 5MP, 15pps @ 3MP, 30pps @ 2MP or 1.3MP
- 2.8 ~ 11mm Vari-focal Lens
- Day/Night functionality with ICR
- 36 IR LEDs (Up to 110ft)
- Back Light Compensation: BLC
- Digital WDR
- Outside PoE / 12VDC
- ONVIF Version 2.2
- Built-in web server for resolution, bit-rate adjustment

CONSTRUCTION:

- 3-Axis Aluminum Bracket (Wire Feed-through)
- Weatherproof - IP66

CLEARLY BETTER:



SMART IR LEDS HAS GOT YOU COVERED

Tired of "hotspots" or too much IR reflection? Our new bullet camer has got you covered - Smart IR LEDs.

All our bullet cameras come equipped with Smart IR LED technology that detects too much IR reflection and automatically compensates.

TECHNICAL SPECIFICATION:

5MP Flexible IP Weatherproof Bullet	NC-5M-B21
Resolution	5MP / 3MP / 2MP / 1.3MP
Image Sensor	1/3" CMOS
Day/Night Functionality	Yes w/ ICR
Lens Type	2.8 ~ 11 mm VF Lens
Angle of View	81° (W) ~ 25° (T)
IR LEDs	36
IR LEDs Distance	Up to 110ft.
LEDs Illumination Angle	80°
Video Compression	H.264 / MJPEG
Frame Rate	10pps@5MP, 15pps@3MP, 30pps@2MP
Electronic Shutter	1/30 ~ 1/20,000 sec.
Minimum Illumination	0.8 Lux (Color), 0.0 Lux (B/W)
Power Over Ethernet (PoE)	IEEE 802.3af compliant
General Information	NC-5M-B21
Operating Temperature	-20°F ~ 122°F
Operating Humidity	Within 90% RH
Power Consumption	Up to 14W / 1A
Input Voltage	POE & 12VDC

*Specifications are subject to change without any prior notice.

DIMENSIONS (INCH:MM):

