**CK-1000** 





## **KEY FEATURES**

- 1 Master with 7 Slave Keyboard Support
- Internal Memory for Download / Save / Upload PTZ Settings (Only available with NUVICO PTZ dome cameras)
- Built-in RS-485 / RS-422 / RS 232 communication ports for operating PTZ Dome Cameras & NUVICO DVRs
- Direct Control of Up to 256 Dome Cameras
- Half Duplex: Up to 64 ID
- Simplex: Up to 256 ID
- Control Up to 99 NUVICO DVRs
- 3-Axis Joystick for Pan/Tilt/Zoom with 64 Variable Speeds
- LCD Display
- User Friendly Design with Clearly Labeled Operation Keys
- · Alarm Acknowledgement
- Keyboard Lock
- User Login Feature
- Real-Time Clock

## **TECHNICAL SPECIFICATIONS**

Technical Specifications	CK-1000
Communications	RS-485 / RS-422 / RS-232
Baud Rates	2,400 ~ Up to 230,000 bps
Joy Stick	3-Axis
Slave Keyboard Support	1 Master, 7 Slave
DVR Control	Up to 99
User Login	Admin / User
Operating Temperature	0°C ~ 50°C
Humidity	Within 90% RH
Features	CK-1000
Dimensions (WxDxH)	16.1" x 7.3" x 4.4"
Power Input	12VDC, 500mA

\*specifications are subject to change without any prior notice.

## **SYSTEM CONFIGURATION**

