

NC-4M-D2



KEY FEATURES:

- 4MP High Resolution
- Triple video stream
- 2.8mm Fixed Lens
- D-WDR
- 2D/3D DNR
- Built-in PoE/12VDC
- Reset button
- 3-Axis Gimbal

TECHNICAL SPECIFICATION

Product Model	HD Fixed Lens IP Camera
Sensor	1/3" 4.0MP CMOS
Min. illumination	Colour:0.05Lux/F1.2: 0Lux/F1.2(IR ON)
Lens	2.8mm Fixed lens
IR distance	100ft
Electronic shutter	Auto(1/10s-1/1000s Adjustable)
Day/Night	Auto/Color / B&W (IR_CUT)
Noise Reduction	2D/3D Digital Noise Reduction
Anti-fog	Support
WDR	Digital WDR
Video Encoding	H.264, MJPEG
Record Resolution	Main Stream:2560*1440@20fps
	Sub Stream: 704*576@20fps
	Third Stream: 1280*720@15fps
Video Bitrate Control	Support VBR/CBR
Video Bitrate Range	32Kbps ~ 8Mbps
Reset Button	Yes
Network Interface	RJ45 10M/100M adaptive Ethernet interface
Snapshot	JPEG capture, capture resolution is the max coding resolution
Alarm	No Support
Mobile APP	IOS, Andriod
Network Function	TCP/IP: UDP: HTTP: IGMP: ICMP: DHCP: RTP/RTSP: DNS
	DDNS: FTP: NTP: PPPOE: UPNP: SMTP: SNMP
Protocol	Support ONVIF and CGI protocol
Protection Grade	IP66
Power	PoE / DC 12V
Operation Temperature	-10 °C ~ +60 °C
Operation Humidity	10% ~ 90%
Power Supply	3W MAX

*Specifications are subject to change without any prior notice.

DIMENSIONS

Unit: Inches (mm)

